

PLACOFINISH

Finishing paste for Plasterboard

Description:

Plaster-based product for a complete finish over plasterboard (PB).

Uses:

As a thin-layer finish to apply on the entire PB surface, including the joint areas.

Advantages:

- Pre-treatment of joints and screws not required.
- Total coverage of the PB provides a smooth surface.
- Surface is highly resistant to impacts and scratches.
- Similar application to a skim-coat finish.
- Surface can be painted directly.

Application:

1. Mix the contents of the bag with approx. 12 litres of water in a flexible bucket. For best results, use mechanical mixing paddle.
2. Put the mesh tape in the joints and cover the joints with Placofinish.
3. Apply the first coat of the product to an approximate thickness of 2 mm.
4. While the first coat is still hardening, apply a second coat approx. 0.5 mm thick.
5. For best results, use a trowel to extend the product while slightly moistening the surface.

For further information, please refer to existing documentation.

Specifications:

- Base: Plaster
- Water mix proportion: 12 litres/sack
- Final hardness: 60-70 Shore D
- Approx. pH: >12 (use gloves and eye protection)
- Mix pot-life: 30 min. (varies depending on working temp.)
- Application cycle time: 2h. 30 min.
- Consumption: 2.5 kg/m²
- Coverage: 10 m²/sack, 480 m²/pallet
- Application temperature: between 5° and 35° C
- Packaging: 25 kg sacks
- Stacking: 48 sacks/pallet
- Shelf life: 6 months, keep sheltered from sun and rain



Iberplaco

Main offices: Paseo Castellana, 77, 28046 Madrid, www.iberplaco.es



Atención al cliente:

902 253 550

902 296 226