

# CONECTOR GYPTONE®

Accessories



## Product Description

Galvanised steel metal accessory manufactured using cold-rolling.

## Application


Installation of Gyptone® hidden edge suspended ceiling (D2)

## Storage and conservation

Never store outdoors. Keep covered and protected from the sun and rain.

## Handling

The use of Category 4 cut resistant gloves is recommended.



<b>Characteristic</b>	<b>Value</b>
Norms	EN 13964, Suspended ceilings. Requirements and test methods
Fire Reaction (EN Standard)	A1
<b>Conditioning</b>	100 Piece/Box

This information and, in particular, the recommendations relating to the application and use of the product, are based on the current technical knowledge and experience of SAINT-GOBAIN PLACO IBERICA S.A., of its products, which must be correctly stored, handled and installed within their useful life. The terms of the General Conditions of Sale and Supply of Saint-Gobain Placo S.A. apply to all orders. SAINT-GOBAIN PLACO IBERICA S.A. reserves the right to change the technical specifications of the product without prior notice. It is the user's responsibility to find out and use the latest and updated version of the product data sheets, a copy of which will be sent to those who request it. The content of this document is not exhaustive. Saint-Gobain Placo S.A. accepts no responsibility in the event of the use of our products in a way that does not conform to the instructions supplied by Saint-Gobain Placo S.A. Within the legal limits, Saint-Gobain Placo S.A. will not be responsible for loss of profit or indirect damages.

