



PLACO® FENIX 15 1200 Boards



Product Description

Laminated plasterboard with double-sided cardboard 15 mm thickness and 1,200 mm in width, appropriately added to provide it with high acoustic performance, robustness grade R3, passive protection and resistance to humidity.

Application

Construction of dry-work systems in interiors: partition walls, partitions, self-supporting cladding, continuous ceilings. It will be used mainly in solutions that require high acoustic insulation performance, high performance against fire, humidity and high surface hardness.

Storage and conservation

Store the boards on flat surfaces and never outdoors, keeping them covered, away from sunlight and rain. Maximum stacking of the boards: 6 pallets.

Conditions of installation

Refer to the Isover and Placo® Installer Manual.



Handling

During the unloading, the aperture of the forks of the forklift should be a minimum of 1/3 of the length of the board being handled, always placing the load in the centre of the forks on the forklift. Special care is advised for handling 3,000 mm boards.

PLACO® FENIX 15 1200

Characteristic	Value
Norms	EN 520, Gypsum plasterboards. Definitions, requirements and test methods
Board thickness	15 mm
Board Thickness Tolerance	±0,5 mm
Board liner color	Blue
Board reverse color	Green
Long Edge Type	Sharp Edge (BA)
Short Edge Type	Square Edge (BC)
Thermal conductivity	0.25 W/m.K
Surface Hardness	Tread diameter ≤15 mm
Water vapour diffusion factor μ	10
Fire Reaction (EN Standard)	A2-s1, d0
CE board type designation	D, I, F, R, H1
Approximate weight per m ²	14.8 kg/m ²
Flexural breaking load longitudinal	≥870 N
Flexural breaking load transversal	≥360 N
R index	R2

Length (mm)	Width (mm)	Packaging Boards/Pallet
2500 ¹	1200 ²	24
3000 ¹	1200 ²	24

¹ Tolerancia del largo (mm): +0/-5

² Width tolerance (mm): +0/-4



Delegación General Mediterránea de Saint-Gobain para España, Italia, Portugal, Grecia, Marruecos, Argelia, Túnez y Libia
c/ Príncipe de Vergara, 132 • 28002 • Madrid • Tel: +34 91 397 20 00 • www.saint-gobain.es

This information and, in particular, the recommendations relating to the application and use of the product, are based on the current technical knowledge and experience of SAINT-GOBAIN PLACO IBERICA S.A. of its products, which must be correctly stored, handled and installed within their useful life. The terms of the General Conditions of Sale and Supply of Saint-Gobain Placo S.A. apply to all orders. SAINT-GOBAIN PLACO IBERICA S.A. reserves the right to change the technical specifications of the product without prior notice. It is the user's responsibility to find out and use the latest and updated version of the product data sheets, a copy of which will be sent to those who request it. The content of this document is not exhaustive. Saint-Gobain Placo S.A. accepts no responsibility in the event of the use of our products in a way that does not conform to the instructions supplied by Saint-Gobain Placo S.A. Within the legal limits, Saint-Gobain Placo S.A. will not be responsible for loss of profit or indirect damages.

18/07/25