



PLACO® PR HYDRO

Plasters



Product Description

1 hour powder setting paste with reduced water absorption capacity intended for joint treatment in H1 Gypsum Plasterboard Systems.

Application

Construction of interior dry systems. Due to its low water absorption, to be used mainly in construction systems in humid rooms. It improves the adhesion of the joint tape in areas of high humidity and is suitable for both filling and finishing the joint, especially in humid areas such as kitchens and bathrooms. It allows the joint to be completed within the day and is suitable for finishing levels Q1, Q2, Q3 and Q4.

Storage and conservation

Store on flat surfaces and never outdoors, keeping the material under cover, away from sunlight and humidity. The maximum shelf life is 9 months from the date of manufacture printed on the bag.



Handling

Wearing gloves and mask is recommended.

Characteristic	Value
Norms	EN 13963, Jointing materials for gypsum plasterboards. Definitions, requirements and test methods
Fire Reaction (EN Standard)	A1
Total water absorption	≤ 5%
Surface water absorption	< 180 g/m ²
Waiting time	10 min
Setting time	1 h
Usable life time after mixing	1 h
Mixture proportion (water/powder)	13 - 14 l/25 kg
Designation	Hydrophobic setting paste (H1), for manual application, type 3B (UNE-EN 13963).
Finish level	Q1 Q2 Q3 Q4

Packaging

Bag	10 ¹	kg
Bag	25 ¹	kg

¹ ± 5%



**PELIGRO
PERIGO**

INDICADORES DE PELIGRO

H318 Provoca lesiones oculares graves.

CONSEJOS DE PRUDENCIA

P102 Mantener fuera del alcance de los niños.

P280 Llevar guantes/prendas/gafas/máscara de protección.

P305+351+338 Contacto con los ojos: Aclarar cuidadosamente con agua durante varios minutos. Quitar las lentes de contacto, si hubiese y es fácil de hacer. Proseguir con el lavado.

INDICADORES DE PERIGO

H318 Provoca graves lesões oculares.

CONSELHOS DE PRECAUÇÃO

P102 Manter afastado do alcance das crianças.

P280 Utilizar luvas, roupa, óculos e máscara de protecção.

P305 + 351 + 338 Contacto com os olhos:

Em caso de contacto com os olhos, lave imediatamente com água em abundância durante vários minutos.

Caso existam lentes de contacto, sendo possível, deve proceder-se à sua remoção e continuar com a lavagem.