



PLACO® RAÍL THR75

Metal profiles



Product Description

Metal profile in Z-275 g/m² galvanised steel, 75 mm width, constituting the horizontal perimeter "U"-shaped element that is screwed into the upper and lower slabs. They ensure the connection and alignment between vertical THM posts in Placotherm® Integra complete sheet façade systems.

Storage and conservation

Store on flat surfaces and never outdoors, keep covered, away from sunlight and rain.

Conditions of installation


Installation using the Placotherm® Integra façade products range is recommended. Please consult the Building Solutions for Laminated Plasterboard Manual, the façade catalogue and the Placo® Installer's Manual.



Characteristic	Value
Norms	EN 14195, Metal framing components for gypsum plasterboard systems - Definitions, requirements and test methods
Fire Reaction (EN Standard)	A1
Type of material	S250GD
Coating type	Z1 = Z-275 / Z2 = Special
Weight per linear meter	0.84 kg
Metal Thickness	0.7 mm
Thickness Tolerance	± 0.05 mm

Length (mm)	Tolerance (mm)	Un/Package	Un/Pallet
3000	± 4	8	240
3000	± 4	8	240

Dimensions (mm)	Dimensions (mm)	Tolerance
a	75.00 mm	± 0.5
Ala b	40.00 mm	± 1
Ala c	40.00 mm	± 1



This information and, in particular, the recommendations relating to the application and use of the product, are based on the current technical knowledge and experience of SAINT-GOBAIN PLACO IBERICA S.A. of its products, which must be correctly stored, handled and installed within their useful life. The terms of the General Conditions of Sale and Supply of Saint-Gobain Placo S.A. apply to all orders. SAINT-GOBAIN PLACO IBERICA S.A. reserves the right to change the technical specifications of the product without prior notice. It is the user's responsibility to find out and use the latest and updated version of the product data sheets, a copy of which will be sent to those who request it. The content of this document is not exhaustive. Saint-Gobain Placo S.A. accepts no responsibility in the event of the use of our products in a way that does not conform to the instructions supplied by Saint-Gobain Placo S.A. Within the legal limits, Saint-Gobain Placo S.A. will not be responsible for loss of profit or indirect damages.