

PLACOSTIC® PRO PINTORES

Plasters

Product Description

Paste for renovation and smoothing.

Application

- Filling holes, chips, scratches, cracks (which will not move), plastering, levelling and smoothing surfaces indoors.
- Renovation of rough walls with godelé or decorated treatments and which require a layer thickness < 5 mm.

Instructions for use:

- 1.- The container where the mixture is prepared must be clean.
- 2.- Add clean water to the container, and sprinkle the product gradually until the paste is formed in a proportion of 0.5 l of water / 1 kg of product.
- 3.- Let the mixture rest for 1.5 - 2 minutes and then beat vigorously by hand or machine until a homogeneous paste is obtained.
- 4.- Spread the paste over the surface evenly, covering the irregularities. Once the first layer has set (approximately 2 hours), apply the second.
- 5.- Wait for the application to dry completely before any subsequent treatment (approximately 24 hours).
- 6.- Sand with fine sandpaper until the desired fineness is obtained.

Storage and conservation

Store on flat surfaces and never outdoors, keeping the material covered and protected from sunlight and moisture. The maximum storage time is 12 months from the date of manufacture printed on the bag.



Conditions of installation

The surface must be healthy and maintain its consistency, being able to support the weight and tension of the layers of product applied later without disintegrating or altering its structure, and therefore it will be necessary to remove poorly adhered layers of paint, paper remains, or any other element that could cause the product to come off once applied.

The surface must be free of dust, grease, fungi, or any other material that could hinder the correct adhesion of the product or cause it to come off later. The surfaces must be cleaned if necessary, until reaching the consistent base.

Large cracks or holes must be treated with a much thicker application of Placostic Standard.

If the surface is very absorbent, the absorption regulator Iberprimer must be applied.

On very smooth surfaces, it is recommended to sand or scratch the surface for greater adhesion.

Handling

It is advisable to use gloves and a mask.

Characteristic	Value
Average consumption when applied (per mm of thickness)	1 kg/m ²
Drying time	Approximately 24 hours depending on the weather (2 hours between layers)
Maximum operating temperature	Entre 5°C - 30°C
Plaster Surface Hardness	70 Shore C
Quantity of water per kg of powder	0,5 L / 1 kg
Weight of bag/bucket	15 kg

This information and, in particular, the recommendations relating to the application and use of the product, are based on the current technical knowledge and experience of SAINT-GOBAIN PLACO IBERICA S.A. of its products, which must be correctly stored, handled and installed within their useful life. The terms of the General Conditions of Sale and Supply of Saint-Gobain Placo S.A. apply to all orders. SAINT-GOBAIN PLACO IBERICA S.A. reserves the right to change the technical specifications of the product without prior notice. It is the user's responsibility to find out and use the latest and updated version of the product data sheets, a copy of which will be sent to those who request it. The content of this document is not exhaustive. Saint-Gobain Placo S.A. accepts no responsibility in the event of the use of our products in a way that does not conform to the instructions supplied by Saint-Gobain Placo S.A. Within the legal limits, Saint-Gobain Placo S.A. will not be responsible for loss of profit or indirect damages.

