



PLACOTHERM® LÁMINA

Product Description

Flexible and waterproof sheet, with low resistance to the passage of water vapor (breathable) and high durability for waterproofing Placotherm® facades.

Application

Auxiliary element for the protection of thermal insulation and metal structures against humidity in façade elements and solutions.

Storage and conservation

Never store outdoors, keeping them covered and protected from the sun and rain.



Conditions of installation

Consult the Installation and documentation guide for Placotherm® façades.

Characteristic

Norms

Fire Reaction (EN Standard)

Value

UNE-EN 13859-2, Flexible sheets for waterproofing - Definitions and characteristics of underlays - Part 2: Underlays for walls.

E

Packaging

75 Square meter/Roll

40 Roll/Pallet

This information and, in particular, the recommendations relating to the application and use of the product, are based on the current technical knowledge and experience of SAINT-GOBAIN PLACO IBERICA S.A. of its products, which must be correctly stored, handled and installed within their useful life. The terms of the General Conditions of Sale and Supply of Saint-Gobain Placo S.A. apply to all orders. SAINT-GOBAIN PLACO IBERICA S.A. reserves the right to change the technical specifications of the product without prior notice. It is the user's responsibility to find out and use the latest and updated version of the product data sheets, a copy of which will be sent to those who request it. The content of this document is not exhaustive. Saint-Gobain Placo S.A. accepts no responsibility in the event of the use of our products in a way that does not conform to the instructions supplied by Saint-Gobain Placo S.A. Within the legal limits, Saint-Gobain Placo S.A. will not be responsible for loss of profit or indirect damages.

